

High Quality SiO₂ Coating for
Textile & Paper
Art. No. 7689 Dura Tex

7689 Dura Tex Textile & Paper coating protects almost any type of textiles from water, dirt, contamination and staining – whilst remaining totally invisible.

It will not affect the appearance, breathability, colour and texture of the fabric; and of course these characteristics ensure that the fabric is easy to maintain. The coating is highly water-resistant and suitable for application to fabrics used in “outdoor” environments. Coated fabrics become resistant to coffee, oils and general contamination.

Examples of Use:

- Clothing
- Household textiles (pillows, furniture), carpets
- Suede/leather
- Paper, cardboard

Product characteristics:

- Strong hydrophobic and oleophobic protection
- Strong non-stick properties
- Food safe (inert)
- Protection of fibres from the infiltration and subsequent bonding of soiling agents

Further properties:

- Invisible to the human eye (coating thickness: 100-150 nm)
- Permanent (UV-stable), very resistant to abrasion
- No change to the hand / texture of the fabric
- Breathable
- Simple application (do-it-yourself)

Application:

Fabrics are presented for coating in a range of “conditions”, some may have been “bleach washed” to create a worn appearance and others may have been very lightly coated with starch at the factory to make the fabric look better on store hanger.

In order to offer optimized performance from our coating all such residue must be completely removed from the fabric before coating. If the coating is applied correctly to a completely clean fabric we can offer between 5 and 40 (Polyester based fabrics provide enhanced washability when coated) short, machine wash cycles at 30°C. Gentle hand or soak washing will always offer less impact to the coating, thus prolonging the life of the coating.

Simple, do-it-yourself application procedure makes it suitable for end-consumers.

1. Manual: Application by fully moistening textiles (spraying or dipping)
2. Industrial: Application using the standard systems

This SiO₂-coating becomes completely bonded / cured after 24 hours. The easy-clean effect should only be tested after this curing period. Very heavy textiles and heavy carpets may take slightly longer to dry in some environments.

Storage Stability:

Unopened original containers can be stored for at least 2 years.
Recommended storage- and transport temperature: +3 to 30°C

Consumption:

Manual + Industrial: Coating offers between 25 and 100 ml/m², depending on absorbency of the substrate. An estimated quantity of approx. 10ml/m² per mm of materials's thickness is a rough guide for standard fabrics.

Product Characteristics:

Permanence and longevity:

- The UV-stability enables functionality for a number of years, approximately the lifetime of the coated surface in non-abrasive environments
- Easy-to-clean effect
- Abrasion-resistant, a solid chemical connection with the substrate enables an excellent abrasion and washing machine-resistance – the coating adheres to the fibres until it is destroyed by external influences.

IMPORTANT NOTICE:

Our explanations correspond to our current knowledge and experience. We are passing it on, however, without obligation, also with regard to third party patent rights. In particular, a warranty of assured quality in the legal sense is not associated with it. The right to make alterations within the framework of technical advances and operational development is reserved. The customer is not released from careful quality examination. The mention of other company names is not a recommendation and does not exclude the use of similar products. We guarantee the quality of our products in accordance with our general sales conditions as a matter of course. The products are ready-to-use. Mixing with other substances or other charges is strictly forbidden.