

	695	706	7622	7637	704	7620	7626
<b>Application</b>	spray, brush, roller	spray, brush, roller	spray, brush, roller	spray, brush, roller	spray, brush, roller	spray, brush, roller	brush, roller, convention or airless spray
<b>Application Temperature</b>	<5°C - 50°C	<15°C - 25°C	<5°C - 30°C	<5°C - 30°C	<5°C - 40°C	<-10°C - 70°C	<-5°C - +60°C
<b>m<sup>2</sup> per liter</b>	5 - 40	50 - 80	10 - 20	10 - 20	20 - 100	8 - 50	8 - 10
<b>Durability</b>	up to 2 years	up to 10 years	up to three years	up to 10 years	5 years +	10 - 20 years	up to 20 years
<b>Curing Time</b>	12 hours	7 days at room temperature	12 hours	12 hours	24 hours	3-6 hours at 20°C	touch dry 3-4 hours, full cure 24 hours
<b>... based</b>	water	solvent	water	water	solvent	solvent	solvent
<b>Available as concentrate</b>	yes, 1:9-1:14 (art. no. 697)	no	no	no	dilutable up to 1:1 with Ethanol or 1-Methoxy-2-Propanol	no	no
<b>Breathable</b>	yes	no	yes	yes	no	yes	yes
<b>Visible</b>	No on most surfaces	yes, glossy	no on most surfaces	no on most surfaces	yes, glossy	might be slightly darker	yes, clearly (glossy)
<b>Topographical / penetrative</b>	Topographical	topographical	topographical	topographical	topographical	penetrative, extreme abrasion-resistant	topographical, very strong bonding
<b>Oil resistant</b>	yes	yes	yes	yes	yes	yes	yes
<b>Frost resistant</b>	yes	yes	yes	yes	yes	yes	yes
<b>Available in RAL colors</b>	no	no	no	no	yes, from 1.000 liter	no	Yes, from 100 liter
<b>Dangerous goods</b>	no	no	no	no	yes	no	no
<b>Application recommendation</b>	concrete, plaster, natural stone (granite, slate, basalt, sandstone,	concrete, plaster, natural stone (granite, slate, basalt, sandstone,	wet room walls, concrete seating in public areas, stone foyer areas	for monuments, Statues, high value stone art works, paving-stone systems and terrace tiles	concrete, plaster, natural stone (granite, slate, basalt, sandstone, limestone), roof tiles, clinker	concrete, tiles (unglazed), roofing tiles, brick/masonry, limestone, sandstone, mineral plaster, natural stone, façade, slate	Graffiti Protection for up to 50 times, for commercial locations, for aluminium siding, (fibre) glass, masonry, metal, street signs, stucco, utility boxes, vinyl siding, wood