



Car, Boat, Camper & Aircraft Coating

Quick and Easy Application, water-based



- Provides excellent gloss with only gentle buffing
- It can be applied immediately after running a car through a car wash. It does not matter if the surface is damp
- Exceptionally easy to apply, simply “wipe and go”
- appr. 100 ml per car

8654 Quick Gloss is a highly innovative coating technology which has been developed for the enhancement of smooth surfaces such as auto / marine paintwork and plastics. It is very easy to apply and highly effective. The treated surfaces show a highly improved hydrophobicity and associated easy clean characteristics. In addition the product gives a higher shine and colour intensity. This coating is more durable than most waterbased technologies and offers good performance for over 6 months when applied to car paintwork (real time testing after 6 months and 5,000 miles of driving. Repeated use of car washing machines will impact on the life of the coating).

Most significantly this coating is exceptionally easy to apply and a car can be fully protected within minutes.

- Functional in a few minutes
- Not silicone based
- Not sensitive to UV
- Thinner than a typical “wax” layer
- More durable than standard auto wax coatings
- Lasts for approximately 6 months
- Re application is very easy
- No VOCs
- For Autos, Marine and Private Aviation

Application:

Use undiluted. Ideal application temperature between 5°C and 35°C (surface temperature). Any residues of polish or wax on the target surface may harm the bonding of the **8654 Quick Gloss** coating. Clean the surface and remove any loose dirt (it is of course best if the coating is applied to a clean surface).

Spray the target surface with a light film of water. Next, spray **8654 Quick Gloss** on the moist surface and buff / dry it immediately with a lint-free cloth (do not use a microfibre cloth). Continue to buff until all droplets disperse. The product is active immediately.

Alternatively, the product can also be applied on a clean, dry surface. If the product dries too rapidly or if there is an over application of the coating, “white stripes” may become visible. They can be eliminated by adding a small amount of new product and polishing the surface again.

The product may be stored for at least 24 months unopened in its original packing.

Protect from frost and direct sunlight.



CCM GmbH

Diepenbroich 8 | D-51491 Overath / Germany

Fon +49 (0) 2206 / 938590-0 | Fax +49 (0) 2206 / 938590-99

www.ccm-international.eu | www.youtube.com/CCMGermay