

Graffiti Protection 7626

Technical Data Sheet

Purpose	A one pack single coat permanent non-sacrificial coating giving excellent protection against fly poster and graffiti attack. The product allows easy repeated removal of graffiti by using water/detergent
Colour	Clear and Pigmented Liquid
Application	Apply by brush, roller, convention or airless spray
Volume Solids	78% Matt; 78% Gloss; 48% pigmented
Recommended Film Thickness	depending on substrate and porosity, normally between 50-80 DFT
Coverage Rate	Theoretical 8 to10 square metres / litre
Drying Time	Touch dry 3 / 4 hours; full cure 24 hours. Recoating (if required) time 3 to 4 hours
Thinners/Brushwash	Disposal
Weight Per Litre	0.90-1.02
Flash Point	Above 64°C
V.O.C	50 grams per litre
Finish	Gloss – Semi Matt
Application Temperature	-5°C / +60°C, All surfaces must be clean and dry, remove any soiling by power
Surface Preparation	wash etc. Any soiling/graffiti apparent on painted surfaces i.e. masonry /rendered walls should be re-painted with good quality masonry exterior paint, prior to application. Non-Darkening Primer should be applied prior to top coat on all sandstone/brick surfaces

Ideal for the following applications:

- Aluminum Siding
- Fibreglass
- Glass
- Masonry (includes brick, marble, stone, tile, granite and concrete)
- Metal
- Street Signs
- Stucco
- Utility Boxes
- Vinyl Siding
- Wood

Attributes:

- Very strong - with just one coat.
- Zero Ghosting
- Single Part System, one coat in most cases (some surfaces may require a non-darkening sealer)
- Open the can, brush it on. No mixing and no messing means less labour cost
- Permanent Protection
- Graffiti can be removed quickly and easily using just water. No e-application required.
- no dangerous goods shipment
- available in all RAL colors